

# APE Model D62-42 Single Acting Diesel Impact Hammer

*D62-42 in a stand-off driving Kingpile.*



## MODEL D62-42 (6.2 metric ton ram)

### SPECIFICATIONS

Stroke at maximum rated energy	144 in (366 cm)
Maximum rated energy (Setting 4)	164,052 ft-lbs (222.42 kNm)
Setting 3	127,653 ft-lbs (172.33 kNm)
Setting 2	101,507 ft-lbs (137.03 kNm)
Minimum rated energy (Setting 1)	76,899 ft-lbs (103.81 kNm)

*(Variable throttle allows for infinite fuel settings)*

Maximum obtainable stroke	150 in (381 cm)
Maximum obtainable energy	178,862 ft-lbs (243 kNm)
Speed (blows per minute)	34-53

### WEIGHTS (Approximate)

Ram	13,671 lbs (6,200 kg)
Anvil	2,425 lbs (1,100 kg)
Anvil cross sectional area	367.94 in <sup>2</sup> (2373.80 cm <sup>2</sup> )
Hammer weight (includes trip device)	29,100 lbs (13,300 kg)
Typical operating (weight with DB32 and pipe insert)	34,402 lbs (15,602 kg)

### CAPACITIES

Fuel tank (runs on diesel or bio-diesel)	25.5 gal (96.52 liters)
Oil tank	8.2 gal (31 liters)

### CONSUMPTION

Diesel or Bio-diesel fuel	5.2 gal/hr (19.68 liters/hr)
Lubrication	0.52 gal/hr (1.96 liters/hr)
Grease	8 to 10 pumps every 20 minutes of operation time.

*Optional Variable Throttle Control.*



*Drive Base Assembly.*



### STRIKER PLATE

Weight	1,036 lbs (470 kg)
Diameter	25 in (63.5 cm)
Area	491 in <sup>2</sup> (3167.74 cm <sup>2</sup> )
Thickness	8 in (20.32 cm)

### CUSHION MATERIAL

Type/Qty	Micarta / 2 each
Diameter	25 in (63.5 cm)
Thickness	1 in (25.4 mm)
Type/Qty	Aluminum / 3 each
Thickness	1/2 in (12.7 mm)
Diameter	25 in (63.5 cm)
Total Combined Thickness	3.5 in (8.89 cm)
Area	491 in <sup>2</sup> (3167.74 cm <sup>2</sup> )
Elastic-modulus	285 ksi (1,965 mpa)
Coeff. of restitution	0.8

### DRIVE CAP

DB 32:	2,436 lbs (1,104 kg)
--------	----------------------

### INSERT WEIGHT

H-Beam insert for 12" (305 mm) and 14" (355 mm):	948 lbs (430 kg)
Large pipe insert for sizes 12" to 24" diameter:	1,830 lbs (830 kg)

### MINIMUM BOX LEAD SIZE/OPERATING LENGTH

Minimum box leader size	8 in x 32 in (20.32 cm x 81.28 cm)
Operating length as described above	374 in (949.96 cm)



Corporate Offices  
7032 South 196th  
Kent, Washington 98032 USA  
(800) 248-8498 & (253) 872-0141  
(253) 872-8710 Fax

Visit our WEB site:  
[www.apeibro.com](http://www.apeibro.com)  
e-mail: [ape@apeibro.com](mailto:ape@apeibro.com)