


DEEP FOUNDATION SOLUTIONS

VIBRATORY HAMMERS • POWER UNITS • AUGER SYSTEMS • DIESEL & HYDRAULIC HAMMERS
DRILL RIGS • HYDRAULIC PILING RIGS • WICK DRAIN INSTALLERS • LEAD SYSTEMS



Service Bulletin

Re: Black Bruin Drill Grease Port Service Intervals



APE recommends using grease having the following requirements:

- 1. Operating temperature range of -40° F 320° F
- 2. Mineral oil based, lithium soap grease
- 3. Consistency class: NLGI # 1
- 4. Meet DIN KP2.5K-30 or ISO-L-XCCIB2.5 standard's specifications.

Grease Procedure

1. Using a low pressure, handheld grease gun, add grease to the grease nipple. Fill until fresh grease exits the 5 psi check valve on top of the drill and grease the bottom of the drill until fresh grease exits the output shaft. (see attached photos)



DEEP FOUNDATION SOLUTIONS

Vibratory Hammers • Power Units • Auger Systems • Diesel & Hydraulic Hammers Drill Rigs • Hydraulic Piling Rigs • Wick Drain Installers • Lead Systems



www.jandm-usa.com





APE HEADQUARTERS KENT, WA (800) 248-8498 • (253) 872-0141 APE CHINA SHANGHAI, CHINA 011-86-21-5677-1221 GULF REGIONAL OFFICE CONROE, TX / GONZALES, LA (832) 724-1044 • (800) 596-2877 APE CANADA EDMONTON, ALBERTA CANADA (780) 474-9888 • (855) 328-9888 APE BRAZIL SAO PAULO, BRAZIL (863) 660-8716 WESTERN REGIONAL OFFICE STOCKTON, CA (888) 245-4401 • (209) 942-2166